



— READ FIRST —

High Power Wireless-300N 600mW USB Adapter

UA600

IMPORTANT:

DO NOT INSERT THE USB ADAPTER UNTIL THE DRIVER HAS BEEN INSTALLED

1 Insert the Setup CD



2 Install Software

The menu page should appear.

Select the instructions for your operating system below and install the driver for the USB adapter.

Windows Instructions: This Side
Mac Instructions: Back Side

Do not insert the USB Adapter until after the software/driver has been fully installed.

3 Follow the Instructions for your Operating System:


Windows 7 and Vista

A. From the Menu page, select **Install Software**




If the Menu page does not appear, browse the CD drive and double-click the **Autoload.exe** file

B. Start the Driver Installation




If prompted, click **Yes** to begin the installation.

C. Continue the Driver Installation




Follow the instructions that appear and click **Install** to continue the installation.

D. Restart your Computer




A prompt will appear asking you to restart your computer. Select **Yes** and click **Finish** to restart.

E. Insert the High Power USB Adapter




After the computer has fully rebooted, locate two available USB ports and insert the USB Adapter. Windows should automatically begin installing the driver for use with the USB Adapter. If only one USB port is available, insert the USB connector labeled **Primary**.

F. Connect to a Wireless Network



Locate the Wireless Icon in the Windows System tray (bottom right-hand corner) and click it to view available wireless networks. Highlight your desired network and click **Connect**.

G. Connect to a Wireless Network



If the network you are trying to connect to has security enabled you will need to enter it here.


Windows XP and 2000

A. From the Menu page, select **Install Software**




If the Menu page does not appear, browse the CD drive and double-click the **Autoload.exe** file

B. Start the Driver Installation




Click **Next** to begin the installation. Follow the instructions that appear and click **Install** to continue.

C. Restart your Computer




A prompt will appear asking you to restart your computer. Select **Yes** and click **Finish** to restart.

D. Insert the High Power USB Adapter




After the computer has fully rebooted, locate two available USB ports and insert the USB Adapter. The Found New Hardware Wizard should appear. If only one USB port is available, insert the USB connector labeled **Primary**.

E. New Hardware Wizard




When the New Hardware Wizard appears and asks to search for software, select **No, not this time**. Click **Next** to continue.

F. New Hardware Wizard




When prompted by the New Hardware Wizard to install the software, select **Install the Software Automatically** (Recommended) and click **Next**.

G. Connect to a Wireless Network



Once Windows has completed the software installation open the **Amped Wireless Utility** on your desktop and open the software by double-clicking the icon. Select the **Available Network** tab to view nearby networks.

H. Connect to a Wireless Network




Highlight the network that you wish to connect to and double-click it to connect. If your network has security enabled, you can enter it in the **Network Key** field and click **OK**.

Installation for Mac Operating Systems


Mac OS X

A. Access the Menu



From the autoloop page, click on [Start Here](#) to open the menu. If the menu does not load browse the CD to find the Start Here file.

B. Find your Operating System Version




Click on the [Apple Icon](#) (upper-left corner). Select [About this Mac](#) and note the Mac OS X version.

C. Select your Operating System




From the CD Menu, select the software version that your Mac is using to begin installing the software (i.e. 10.7, 10.6, 10.5 or 10.4).

D. Find the Folder on the Setup CD




Open your OS X version folder, and then click Installation file to begin the installation.

E. Install the Software




Follow the instructions and click [Continue](#) to install the software. If prompted, select a destination for the driver software. This is typically the Macintosh HD. Click [Continue](#).

F. Restart your Computer




When the software has installed, you will be asked to restart your Mac. Click [Restart](#) to reboot your computer.

G. Turn Off Your AirPort Card




After the computer reboots, disable any AirPort cards by selecting the wireless icon (upper right-corner) and select [Turn AirPort Off](#). If you do not have an Airport Card continue to Step H.

H. Insert the High Power USB Adapter




Once all Airport cards are disabled, insert the High Power USB Adapter into your USB port. Locate two available USB ports and connect the adapter to your computer. If only one USB port is available, only insert the USB connector labeled [Primary](#).

I. Activate the USB Adapter



You may be prompted to activate your USB Adapter in Network Preferences. If not, select the [Apple Button](#) (upper left corner) and select [System Preferences](#) from the drop-down list. From there, select [Network](#).


J. Activate the USB Adapter



For OS X 10.4 Tiger and 10.5 Leopard: Select [Ethernet Adapter \(en#\)](#) and click [Advanced](#). Continue to Step K


For OS X 10.6 Snow Leopard and 10.7 Lion: Select [11n Adapter](#) and click [Apply](#). Continue to Step M

K. Activate the Adapter (OS X 10.4/10.5 Only)




In the Advanced menu, check that the adapter is [Using DHCP](#) and then click [OK](#).

L. Activate the Adapter (OS X 10.4/10.5 Only)



Click [Apply](#) to activate your USB Adapter.


M. Connect to a Wireless Network



The Amped Wireless Utility should automatically load. If it does not load, click the [Amped Wireless Utility icon](#) to load the utility. Select the [Available Network](#) tab to view nearby wireless networks. Highlight your desired network and click [Connect](#).

Note: Click [Add to Profile](#) after highlighting your network to save it and have the Utility connect automatically when in range.

N. Connect to a Wireless Network



If your network has security enabled, enter the security key here. Re-enter it again to confirm. Click [OK](#) to begin using your new wireless adapter.

How to Upgrade your Antenna

Upgrading your antenna can provide more range and distance for different types of wireless applications. The Amped Wireless High Power USB Adapter is compatible with any High Gain 2.4GHz Wi-Fi antenna with a RP-SMA connector. Simply unscrew the original antenna and screw on the upgraded antenna for more range and distance. For more information on High Gain antennas visit the Amped Wireless website.



Using the Adapter with only One USB Connector

The High Power 600mW USB Adapter features two USB connectors for providing the maximum performance through the power of two USB ports. However, in the case that you wish to only use one USB connection, simply insert only the USB connector labeled "PRIMARY." For full range and performance the USB connector labeled "AMPED" must also be inserted.

